

**M12 female 0° A-cod. with cable**

PVC 5x0.34 gy 30m

Female straight

M12, 5-pole


A-coded

Art-No. 7005 - M12 Lite - (plastic hexagonal screw) on request

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

**[Link to Product](#)****Illustration**

(\* for cable type 126, 732, 219, 619, 729)

**Female**

Product may differ from Image



\* only for products with UL/CSA approved cable

**Form**

Form

12241

**Technical Data**

|   |  |
|---|--|
| Operating voltage                         | max. 125 V AC/DC   |
| Operating voltage (only UL listed)        | max. 30 V AC/DC  |
| Rated surge voltage                       | 1.5 kV   |
| Operating current per contact             | max. 4 A   |
| No. of poles                              | 5  |
| Material group                            | IEC 60664-1, category I  |
| Coding                                    | A-coded  |
| LED display                               | no   |
| Locking of ports                          | Screw thread (M12×1 mm) recommended torque 0.6 Nm, self-securing |
| Compression gland                         | M12 (SW13)   |
| Protection                                | IP65, IP66K, IP67 inserted and tightened (EN 60529)              |
| Material                                  | PUR  |
| Locking material                          | Zinc die casting, matte nickel plated                            |
| suitable for corrugated tube (internal Ø) | 10 mm  |

#### General data

|                            |  |
|----------------------------|--|
| Standards                  | DIN EN 61076-2-101 (M12)                 |
| Mounting method            | inserted, tightened                      |
| Material (contact)         | Copper alloy                             |
| Material (contact surface) | Au                                       |
| Material (gasket)          | FKM                                      |
| Pollution Degree           | 3  |
| Stripping length (jacket)  | 20 mm                                    |
| Temperature range          | -25...+85 °C, depending on cable quality |

#### Cables

|                            |                          |
|----------------------------|--------------------------|
| No./diameter of wires      | 5 × 0.34 mm <sup>2</sup> |
| Wire isolation             | PVC (br, wh, bl, bk, gr) |
| Outer Ø                    | 5.9 mm ±5%               |
| Cable number               | 344                      |
| Approval (cable)           | CE conform               |
| Color (jacket)             | gray                     |
| Jacket Color               | gray                     |
| Temperature range (fixed)  | -30...+80 °C             |
| Temperature range (mobile) | -5...+70 °C              |
| Bend radius (fixed)        | 10 × outer Ø             |
| Bend radius (moving)       | 15 × outer Ø             |
| Material (jacket)          | PVC                      |

#### Commercial data

|                       |               |
|-----------------------|---------------|
| country of origin     | CZ            |
| customs tariff number | 85444290      |
| EAN                   | 4048879669313 |
| eClass                | 27279218      |
| Packaging unit        | 1.000         |