

MODLINK MSDD DATA INSERT

1xUSB-A female/female + 1xSUB-D25 female/male

USB (form A); SUB-D25

1× USB 3.0 (female/female) form A

1× SUB-D25 (female/male)

Link to Product

Illustration



Product may differ from Image



General data

Dimensions H×W×D 88×51×70.4 mm

USB

| | |
|-------------------------------|--------------------------|
| Operating voltage | 48 V AC/DC |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC |
| Operating current | 1.5 A |
| Locking of ports | Snap In |
| Specification | USB: 3.0 (max. 5 Gbit/s) |

Shielding plate

| | |
|-------------------|------------------|
| Connection | Threaded hole M4 |
| Tightening torque | 0.9 Nm ±0.1 |

SUB-D25

| | |
|-------------------------------|------------------------|
| Operating voltage | 48 V AC/DC |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC |
| Operating current | 3 A |
| Operating current (UL Rating) | max. 175 mA |
| No. of poles | 25-pole |
| Connection front side | SUB-D (female) |
| Connection rear side | SUB-D (male) |
| Locking of ports | UNC 4...40 bolt |

Commercial data

| | |
|-----------------------|---------------|
| country of origin | DE |
| customs tariff number | 85366990 |
| EAN | 4048879037730 |
| eClass | 27189217 |
| Packaging unit | 1 |