

**MSUD valve plug CI-9.4mm with cable**

PVC 3x0.75 bk 5m

MSUD

Form CI (9.4 mm)

24 V AC  $\pm 20\%$  / DC  $\pm 25\%$ 

LED and suppression

Further cable lengths on request.

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

[Link to Product](#)**Illustration**

Product may differ from Image

**Form**

Form 94031

**Technical Data**Operating voltage 24 V AC  $\pm 20\%$  / DC  $\pm 25\%$ 

Rated surge voltage 0.8 kV

Operating current per contact max. 4 A

Switch off peak max. 55 V

|                       |   |
|-----------------------|---|
| Locking of ports      | M3 (recommended torque 0.4 Nm)                |
| Protection            | IP66K, IP67 inserted and tightened (EN 60529) |
| Housing               | Black plastic (gray on request)               |
| Switch off delay time | max. 20 ms                                    |

**General data**

|                   |  |
|-------------------|--|
| Temperature range | -25...+85 °C, depending on cable quality |
|-------------------|--|

**Cables**

|                                    |  |
|------------------------------------|--|
| No./diameter of wires              | 3× 0.75 mm <sup>2</sup>                          |
| Wire isolation                     | PVC (bk num, gnye)                               |
| Outer Ø                            | 5.9 mm ±5%                                       |
| Cable identification               | 616  |
| Cable Type                         | 1 (PVC)  |
| Approval (cable)                   | CE conform                                       |
| Cable weight [g/m]                 | 61,6 g   |
| Material (wire)                    | Cu wire, bare                                    |
| Resistor (core)                    | max. 26 Ω/km (20 °C)                             |
| Single wire Ø (core)               | 0.2 mm   |
| Construction (core)                | 24× 0.2 mm (multi-strand wire class 5)           |
| Diameter (core)                    | 3× 0.75 mm <sup>2</sup>                          |
| AWG                                | similar to AWG 18                                |
| Material (wire isolation)          | PVC  |
| Material property (wire isolation) | CFC-, cadmium-, silicone- and lead-free          |
| Shore hardness (wire isolation)    | 43 ±5 D  |
| Wire-Ø incl. isolation             | 1.8 mm ±5%                                       |
| Color/numbering of wires           | bk numbered, gnye longitudinally striped         |
| Stranding combination              | 3 wires twisted                                  |
| Shield                             | no   |
| Material (jacket)                  | PVC  |
| Material property (jacket)         | CFC-, cadmium-, silicone- and lead-free          |
| Shore hardness (jacket)            | 80 ±5 A  |
| Outer-Ø (jacket)                   | 5.9 mm ±5%                                       |
| Color (jacket)                     | black  |
| Cable labeling                     | see frame delivery specifications 7000-00000-001 |
| Jacket Color                       | black  |
| chemical resistance                | good resistance to oil, gasoline and chemicals   |
| Nominal voltage                    | 300/500 V AC                                     |
| Test voltage                       | 3000 V AC  |
| Current load capacity              | to DIN VDE 0298-4                                |
| Temperature range (fixed)          | -30...+70 °C                                     |
| Temperature range (fixed)          | -30...+70 °C                                     |
| Temperature range (mobile)         | -5...+70 °C                                      |
| Temperature range (mobile)         | -5...+70 °C                                      |
| Bend radius (fixed)                | 5× outer Ø                                       |
| Bend radius (moving)               | 10× outer Ø                                      |
| Bend radius (moving)               | 10× outer Ø                                      |
| Material (jacket)                  | PVC  |

**Commercial data**

|                       |               |
|-----------------------|---------------|
| country of origin     | CZ            |
| customs tariff number | 85444290      |
| EAN                   | 4048879114936 |
| eClass                | 27279218      |
| Packaging unit        | 1.000         |