

Modlink MSDD-set: Frame 4000-68122-0000000,

insert 4000-68000-0740000 + 4000-68000-0010000

[Link to Product](#)

Illustration



Product may differ from Image

Frame

The information in this brochure has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

Murrelektronik Ltd. | 5 Albion Street, Pendlebury Industrial Estate, Swinton | Manchester M27 4FG | Fon +44 161 728 3133 | Fax +44 161 728 3130 | shop@murrelektronik.co.uk | shop.murrelektronik.co.uk

| | |
|---|---|
| suitable for mounting with wall thickness | 1...5 mm |
| Protection | IP65 |
| Housing | Zinc die-casting, KTL coated |
| Temperature range | -10...+60 °C (storage temperature -25...+60 °C) |

Germany (VDE)

| | |
|-------------------|---|
| Operating voltage | 250 V AC |
| Operating current | 16 A |
| No. of poles | 2 + PE |
| Connection | Screw terminals: max. 2× 6 mm ² (AWG 10) |
| LED display | yellow |

SUB-D25

| | |
|-------------------------------|------------------------|
| Operating voltage | 48 V AC/DC |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC |
| Operating current | 3 A |
| Operating current (UL Rating) | max. 175 mA |
| No. of poles | 25-pole |
| Connection front side | SUB-D (female) |
| Connection rear side | SUB-D (male) |
| Locking of ports | UNC 4...40 bolt |

Commercial data

| | |
|-----------------------|---------------|
| country of origin | CZ |
| customs tariff number | 85366990 |
| EAN | 4048879035507 |
| eClass | 27189217 |
| Packaging unit | 1 |