


**M12-DISTRIBUTOR BOX 4-WAY, 5-POLE WITHOUT LED**

MVC4-UQQ5.0-XA 5m PUR-CNOMO-cable 8x0,34/3x1

4-way, 5-pole  
PUR/PVC (CNOMO)  
5.0 m  
without LED

[Link to Product](#)**Illustration****M12 Females 5-pole**

Product may differ from Image

**Technical Data**

Operating voltage	24 V DC
Operating current per contact	max. 4 A
Locking of ports	Screw thread (M12x1 mm)
Signal per port	2
Total current	max. 10 A

**General data**

Temperature range	-20...+80 °C
Protection	IP67 inserted and tightened (EN 60529)
Dimensions HxWxD	117x54x33 mm

**Cables**

No./diameter of wires	8x 0.34 + 3x 1.0 mm <sup>2</sup>
Outer Ø	11.0 mm ±5%
Bend radius (moving)	15x outer Ø
Material (jacket)	PUR/PVC

**Contact Layout**

PIN 1	(+)
PIN 2	(NC)/(S2)
PIN 3	(-)
PIN 4	(NO)/(S1)
PIN 5	(Earth)

**Commercial data**

country of origin	CZ
customs tariff number	85444290
EAN	4048879000178

---

eClass	27279219
Packaging unit	1.000

---