

MODLINK MSDD DATA INSERT

1×SUB-D9 fem./fem. + 1×RJ45 + 1×BNC fem./fem.

BNC; RJ45; SUB-D9

1× BNC (female/female)

1× RJ45, 8-pole metal, CAT5e (female/female)

1× SUB-D9 (female/female)

Link to Product**Illustration**

Product may differ from Image

General data

Dimensions H×W×D	88×51×33 mm
------------------	-------------

RJ45

Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

BNC

Connection rear side	BNC (female)
No. of poles	2 + PE
Connection front side	BNC (female)
Operating current (UL Rating)	max. 175 mA
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Locking of ports	Snap In

SUB-D9

Connection rear side	SUB-D (female)
Operating current (UL Rating)	max. 175 mA
Connection front side	SUB-D (female)
Locking of ports	UNC 4...40 bolt
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current	3 A
No. of poles	9-pole
Operating voltage	48 V AC/DC

Commercial data

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

country of origin	CN
customs tariff number	85366990
EAN	4048879037389
eClass	27189217
Packaging unit	1.000