

MODLINK MSDD DATA INSERT

1×SUB-D9fem./fem.+1×SUB-D9male/male+1×RJ45+1×USB-A

RJ45; USB (A); SUB-D9; SUB-D9
 1× RJ45, 8-pole metal, CAT5e (female/female)
 1× USB 2.0 (female/female) form A
 1× SUB-D9 (female/female)
 1× SUB-D9 (male/male)

Link to Product

Illustration



Product may differ from Image

General data

Dimensions H×W×D 88×51×45 mm

RJ45

Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

SUB-D9

Operating current (UL Rating)	max. 175 mA
Locking of ports	UNC 4...40 bolt
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current	3 A
No. of poles	9-pole
Operating voltage	48 V AC/DC

USB

Operating current	max. 500 mA
Specification	USB: 2.0 (max. 480 Mbit/s)
Locking of ports	Snap In
Operating voltage	48 V AC/DC
Operating voltage (UL Rating)	42.4 V DC

Shielding plate

Tightening torque	0.9 Nm ±0.1
-------------------	-------------

Connection Threaded hole M4

Commercial data

country of origin	DE
customs tariff number	85366990
EAN	4048879037631
eClass	27189217
Packaging unit	1.000