

**M23 FEMALE 0° 6POLE**

PVC (4G1,5+(2x1,5)C)C 12m

Power cable with brake wires for SINAMICS S120 and motors with M23 connection and holding brake

Female straight

M23, 6-pole

without cable sleeves


Further cable lengths on request.

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

[Link to Product](#)**Illustration**

Female



Product may differ from Image

**Form**

Form PS501

**Technical Data**

|                                           |                                                                                                                |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Operating voltage                         | 600 V AC/DC (PIN 1/2/3/6); 250 V AC/DC (PIN 4/5)                                                               |
| Rated surge voltage                       | 4 kV (PIN 1/2/3/6); 2 kV (PIN 4/5)                                                                             |
| Operating current per contact             | Power cores: 12 A (1.5 mm <sup>2</sup> ), 15 A (2.5 mm <sup>2</sup> ); brake cores: 5 A (1.5 mm <sup>2</sup> ) |
| Material group                            | IEC 60664-1, category I                                                                                        |
| Locking of ports                          | Screw thread (M23×1 mm) recommended torque 2.0 Nm, self-securing                                               |
| Compression gland                         | M23 (SW27)                                                                                                     |
| Protection                                | IP65 and IP67 when plugged and screwed down (EN 60529)                                                         |
| Locking material                          | Brass, nickel plated                                                                                           |
| Material                                  | PUR                                                                                                            |
| suitable for corrugated tube (internal Ø) | 16 mm                                                                                                          |

**General data**

Pollution Degree 3

Temperature range -25...+85 °C, depending on cable quality

#### Cables

|                            |                                 |
|----------------------------|---------------------------------|
| Cable number               | 861                             |
| No./diameter of wires      | (4G1.5 + (2× 1.5)C)-C           |
| Wire isolation             | TPM (bk num, gnye)              |
| C-track properties         | 0.1 Mio.                        |
| Torsion stress             | ±30°/m                          |
| Jacket Color               | orange                          |
| Material (jacket)          | PVC (UL/CSA) (=MC500)           |
| Specification              | 6FX5008-1BA11                   |
| Outer Ø                    | 10.4 mm ±5%                     |
| Bend radius (fixed)        | 5× outer Ø                      |
| Bend radius (moving)       | 18× outer Ø                     |
| Temperature range (fixed)  | -40...+80 °C                    |
| Temperature range (mobile) | -20...+60 °C                    |
| Shield                     | yes                             |
| Approval (cable)           | UL (AWM-Style 2570/10492), CSA  |
| Diameter (core)            | 4× 2.5 + 2× 1.5 mm <sup>2</sup> |

#### Commercial data

|                       |               |
|-----------------------|---------------|
| country of origin     | DE            |
| customs tariff number | 85444290      |
| EAN                   | 4048879629966 |
| eClass                | 27279218      |
| Packaging unit        | 1             |