

MODLINK MSDD DATA INSERT

1×SUB-D9 fem./fem. + 1×RJ12 + 1×USB-A fem./fem.

USB (form A); SUB-D9; RJ12
 1× USB 2.0 (female/female) form A
 1× SUB-D9 (female/female)
 1× RJ12 (6-pole plastic)

Link to Product**Illustration**

Product may differ from Image

General data

Dimensions H×W×D 88×51×45 mm

SUB-D9

Operating voltage	48 V AC/DC
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current	3 A
Operating current (UL Rating)	max. 175 mA
No. of poles	9-pole
Connection front side	SUB-D (female)
Connection rear side	SUB-D (female)
Locking of ports	UNC 4...40 bolt

RJ12

Operating voltage	max. 48 V AC/DC
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current	max. 1 A
Operating current (UL Rating)	max. 175 mA
Connection front side	RJ12
Connection rear side	RJ12
Locking of ports	Snap In

USB

Operating voltage	48 V AC/DC
Operating voltage (UL Rating)	42.4 V DC
Operating current	max. 500 mA
Locking of ports	Snap In
Specification	USB: 2.0 (max. 480 Mbit/s)

Shielding plate

The information in this brochure has been compiled with the utmost care.
 Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

Connection	Threaded hole M4
Tightening torque	0.9 Nm \pm 0.1

Commercial data

country of origin	DE
customs tariff number	85366990
EAN	4048879037495
eClass	27189217
Packaging unit	1