

Main

Range	TeSys
Device short name	GK2AX
Product or component type	Fault signalling contact
Product compatibility	GK3EF
Auxiliary contacts operation	Fault signal 1 NO
Pole contact composition	1 NO
Connections - terminals	Screw clamp terminals 2 cable 2.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 2.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 2.5 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 1...4 mm ² - cable stiffness: solid
Quantity per set	Set of 10

Complementary

Mounting location	Left side
[Ui] rated insulation voltage	500 V - conforming to IEC 60947-1
[Ue] rated operational voltage	500 V
[Ith] conventional free air thermal current	6 A
Protection type	GG fuse <= 6 A GB2CB... circuit breaker rating according to operational current for Ue <= 415 V
Rated operational power in VA	700 VA at 500 V AC-15 - electrical durability: 20000 cycles 700 VA at 440 V AC-15 - electrical durability: 20000 cycles 850 VA at 380...415 V AC-15 - electrical durability: 20000 cycles 800 VA at 220...240 V AC-15 - electrical durability: 20000 cycles 500 VA at 110...127 V AC-15 - electrical durability: 20000 cycles 360 VA at 48 V AC-15 - electrical durability: 20000 cycles
Rated operational power in W	120 W at 220 V DC-13 - electrical durability: 1000 cycles 140 W at 110 V DC-13 - electrical durability: 1000 cycles 180 W at 60 V DC-13 - electrical durability: 1000 cycles 240 W at 48 V DC-13 - electrical durability: 1000 cycles 180 W at 24 V DC-13 - electrical durability: 1000 cycles
Height	80 mm
Width	8.8 mm
Depth	105 mm
Product weight	0.025 kg

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------