

Cube67 I/O Cable-Module, I/O Extension Module

DIO8, M12 , M12 8 pol., 0,5m

Expansion module

DIO8 - 60 mA (E) 0.5 m (M12)

8-pole

Digital inputs/outputs (multifunctional)

Connection cables are in the online shop under "Connection Technology".

Housing fully potted.

Link to Product

Illustration



Product may differ from Image



General data

Mounting method	2-hole screw mounting
Temperature range	0...+55 °C (storage temperature -20...+75 °C)
Protection	IP67
Dimensions HxWxD	150x30x34.5 mm

Output

Actuator supply UA	24 V DC (EN 61131-2), via system connection (max. 4 A)
Switching current per output	max. 60 mA (short-circuit and overload protected)

Input

Sensor supply US	24 V DC (EN 61131-2), max. 0.5 A
Type	for 3-wire sensors or mechanical switches, PNP
Input filter	1 ms

Cables

No./diameter of wires	8x 0.25 mm ²
Material (jacket)	PUR
Cable Length	0.5 m

Internal communication

LED display	US: sensor supply and internal supply voltage (green: OK); UA: actuator supply (green: OK)
Current consumption	max. 50 mA

Parameterization

I/O channels	Input/Output
--------------	--------------

Connections

Fieldbus	via internal system connection
Sensor-system/actuator supply	via internal system connection (max. 2x 4 A)

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

Murrelektronik Ltd. | 5 Albion Street, Pendlebury Industrial Estate, Swinton | Manchester M27 4FG | Fon +44 161 728 3133 | Fax +44 161 728 3130 | shop@murrelektronik.co.uk | shop.murrelektronik.co.uk

I/O ports M12 (male) 8-pole, A-coded

Diagnostic

Communication status	via LED
Diagnostic via LED	per module
Diagnostic via BUS	per module and channel
Actuator warning	per channel via BUS
Monitoring - under voltage	yes
Monitoring - no voltage	yes
Short-circuit and overload	yes

Commercial data

country of origin	CZ
customs tariff number	85444290
EAN	4048879330343
eClass	27242604
Packaging unit	1.000