

MODLINK MSDD DATA INSERT

1xUSB-A female/female + 1xSUB-D9 female/soldering

USB (form A); SUB-D9

1 × USB 2.0 (female/female) form A

1 × SUB-D9 (solder connection/female)

[Link to Product](#)**Illustration**

Product may differ from Image

General data

Dimensions H×W×D 88×51×70.4 mm

SUB-D9

| | |
|-------------------------------|---------------------------|
| Operating voltage | 48 V AC/DC |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC |
| Operating current | 3 A |
| Operating current (UL Rating) | max. 175 mA |
| No. of poles | 9-pole |
| Connection front side | SUB-D (female) |
| Connection rear side | SUB-D (solder connection) |
| Locking of ports | UNC 4...40 bolt |

USB

| | |
|-------------------------------|----------------------------|
| Operating voltage | 48 V AC/DC |
| Operating voltage (UL Rating) | 42.4 V DC |
| Operating current | max. 500 mA |
| Locking of ports | Snap In |
| Specification | USB: 2.0 (max. 480 Mbit/s) |

Commercial data

| | |
|-----------------------|---------------|
| country of origin | CZ |
| customs tariff number | 85366990 |
| EAN | 4048879037723 |
| eClass | 27189217 |
| Packaging unit | 1 |