

**MODLINK MSDD DBL COMBI INSERT FRANCE**

1xRJ45+USB-A + RCD opening

1 × France (UTE-NF) white  
 1 × RJ45, 8-pole metal, CAT5e (female/female)  
 1 × USB 3.0 (female/female) form A  
 1 × FI cut-out

**[Link to Product](#)****Illustration**

Product may differ from Image

**General data**

Dimensions H×W×D	88×116×70 mm
------------------	--------------

**RJ45**

Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

**USB**

Operating current	1.5 A
Specification	USB: 3.0 (max. 5 Gbit/s)
Locking of ports	Snap In
Operating voltage	48 V AC/DC
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC

**France (UTE-NF)**

Connection	Screw terminals: max. 2 × 4 mm <sup>2</sup> (AWG 12)
Operating current	16 A
No. of poles	2 + PE
Operating voltage	250 V AC

**Shielding plate**

Tightening torque	0.9 Nm ±0.1
Connection	Threaded hole M4

**Commercial data**

country of origin	DE
-------------------	----

customs tariff number	85366990
EAN	4048879446341
eClass	27189217
Packaging unit	1.000