

**M8 female 0° A-cod. with cable LED**

PVC 3x0.25 bk UL/CSA 7m

Female straight

M8, 3-pole

2× LED (PNP)

Art-No. 7005 - M8 Lite - (plastic hexagonal screw) on request

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

**[Link to Product](#)****Illustration**

Female



Product may differ from Image



\* only for products with UL/CSA approved cable

**Form**

Form

08111

**Technical Data**

|  |   |
|--|---|
| Operating voltage                                      | 24 V DC $\pm 25\%$  |
| Rated surge voltage                                    | 0.8 kV  |
| Operating current per contact                          | max. 4 A  |
| Material group   | IEC 60664-1, category I   |
| LED display  | (yellow/green)  |
| Locking of ports                                       | Screw thread (M8x1 mm) recommended torque 0.4 Nm, self-securing |
| Compression gland                                      | M8 (SW9)  |
| Protection   | IP67 inserted and tightened (EN 60529)                          |
| Material   | PUR   |
| Locking material                                       | Zinc die casting, matte nickel plated                           |
| suitable for corrugated tube (internal $\varnothing$ ) | 6.5 mm  |

**General data**

|                   |  |
|-------------------|--|
| Standards         | DIN EN 61076-2-104 (M8)                  |
| Pollution Degree  | 3  |
| Temperature range | -25...+85 °C, depending on cable quality |

**Cables**

|                                     |  |
|-------------------------------------|--|
| No./diameter of wires               | 3x 0.25 mm <sup>2</sup>                        |
| Wire isolation                      | PVC (br, bl, bk)                               |
| Outer $\varnothing$                 | 4.5 mm $\pm 5\%$                               |
| Cable identification                | 610  |
| Cable Type                          | 1 (PVC)  |
| Approval (cable)                    | UL (AWM-Style 2464/1731), CSA                  |
| Cable weight [g/m]                  | 29,37 g  |
| Material (wire)                     | Cu wire, bare                                  |
| Resistor (core)                     | max. 79 $\Omega$ /km (20 °C)                   |
| Single wire $\varnothing$ (core)    | 0.15 mm  |
| Construction (core)                 | 14x 0.15 mm (multi-strand wire class 5)        |
| Diameter (core)                     | 3x 0.25 mm <sup>2</sup>                        |
| AWG                                 | similar to AWG 24                              |
| Material (wire isolation)           | PVC  |
| Material property (wire isolation)  | CFC-, cadmium-, silicone- and lead-free        |
| Shore hardness (wire isolation)     | 45 $\pm 5$ D                                   |
| Wire- $\varnothing$ incl. isolation | 1.25 mm $\pm 5\%$                              |
| Color/numbering of wires            | br, bk, bl                                     |
| Stranding combination               | 3 wires twisted                                |
| Shield                              | no   |
| Material (jacket)                   | PVC  |
| Material property (jacket)          | CFC-, cadmium-, silicone- and lead-free        |
| Shore hardness (jacket)             | 85 $\pm 5$ A                                   |
| Outer- $\varnothing$ (jacket)       | 4.5 mm $\pm 5\%$                               |
| Color (jacket)                      | black  |
| Jacket Color                        | black  |
| chemical resistance                 | good resistance to oil, gasoline and chemicals |
| thermal resistance                  | flame retardant UL 1581 VW1 / CSA FT1          |
| Nominal voltage                     | UL 300 V AC                                    |
| Test voltage                        | 2000 V AC                                      |
| Current load capacity               | to DIN VDE 0298-4                              |
| Temperature range (fixed)           | -30...+80 °C                                   |
| Temperature range (fixed)           | -30...+80 °C                                   |
| Temperature range (mobile)          | -5...+80 °C                                    |
| Temperature range (mobile)          | -5...+80 °C                                    |
| Bend radius (fixed)                 | 5x outer $\varnothing$                         |
| Bend radius (moving)                | 10x outer $\varnothing$                        |

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

|                        |               |
|------------------------|---------------|
| Bend radius (moving)   | 10× outer Ø   |
| Material (jacket)      | PVC (UL/CSA)  |
| <b>Commercial data</b> |               |
| country of origin      | DE            |
| customs tariff number  | 85444290      |
| EAN                    | 4048879842792 |
| eClass                 | 27061801      |
| Packaging unit         | 1.000         |