

**MVP12, 6XM12, 5POLE, PLUGGABLE CABLE**



10.0m PUR/PVC 12x0,34+3x0,75

6-way, 5-pole

PUR/PVC

10.0 m

with LED for digital PNP-signals 24 V DC

[Link to Product](#)**Illustration****M12 Females 5-pole**

Product may differ from Image



UL

UL

**Technical Data**

Operating voltage	24 V DC $\pm 25\%$
Operating current per contact	max. 4 A
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)
Material	PBT
Housing	Plastic, flame retardant
Signal per port	2
Total current	max. 8 A

**General data**

Temperature range	-20...+80 °C
Dimensions HxWxD	125x50.2x17 mm

**Cables**

No./diameter of wires	12× 0.34 + 3× 0.75 mm <sup>2</sup>
Wire isolation	PVC (yebr, rd, grpk, wh, rdbl, gn, whgn, ye, brgn, gr, whye, pk, br, gnye, bl)
C-track properties	2 Mio.
Outer Ø	9.8 mm ±5%
Cable number	388
Color (jacket)	gray
Jacket Color	gray
Temperature range (fixed)	-30...+80 °C
Temperature range (mobile)	-5...+70 °C
Bend radius (fixed)	10× outer Ø
Bend radius (moving)	12× outer Ø
Material (jacket)	PUR/PVC

**Commercial data**

country of origin	CZ
customs tariff number	85444290
EAN	4048879064484
eClass	27279219
Packaging unit	1.000