

**Modlink MSDD-set: Frame 4000-68112-0000000,**

insert 4000-68000-1430000

[Link to Product](#)**Illustration**

Product may differ from Image

**Frame**

|   |   |
|---|---|
| suitable for mounting with wall thickness | 1...5 mm  |
| Protection                                | IP65  |
| Temperature range                         | -10...+60 °C (storage temperature -25...+60 °C) |
| Housing                                   | Zinc die-casting, KTL coated                    |

**RJ45**

|                               |                                       |
|-------------------------------|---------------------------------------|
| Operating current (UL Rating) | max. 175 mA                           |
| Locking of ports              | Snap In                               |
| Connection front side         | RJ45                                  |
| Connection rear side          | RJ45                                  |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC                |
| Specification                 | CAT5e, Class D, 100 MHz, (EN 50173-1) |

**SUB-D9**

|                      |              |
|----------------------|--------------|
| Connection rear side | SUB-D (male) |
|----------------------|--------------|

|                               |                        |
|-------------------------------|------------------------|
| Operating current (UL Rating) | max. 175 mA            |
| Connection front side         | SUB-D (female)         |
| Locking of ports              | UNC 4...40 bolt        |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC |
| Operating current             | 3 A                    |
| No. of poles                  | 9-pole                 |
| Operating voltage             | 48 V AC/DC             |

**USB**

|                               |                          |
|-------------------------------|--------------------------|
| Operating current             | 1.5 A                    |
| Specification                 | USB: 3.0 (max. 5 Gbit/s) |
| Locking of ports              | Snap In                  |
| Operating voltage             | 48 V AC/DC               |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC   |

**Shielding plate**

|                   |                  |
|-------------------|------------------|
| Tightening torque | 0.9 Nm $\pm$ 0.1 |
| Connection        | Threaded hole M4 |

**Commercial data**

|                       |               |
|-----------------------|---------------|
| country of origin     | CZ            |
| customs tariff number | 85366990      |
| EAN                   | 4048879036450 |
| eClass                | 27189217      |
| Packaging unit        | 1.000         |