



Main

Product or component type	Additional output module
Range compatibility	Altivar Easy 610 Altivar Process ATV600 Altivar Process ATV900
Input/Output type	3 relay output(s)
Discrete output number	3
Discrete output type	(R4, R5, R6) relay normally open, sampling time: <= 1 ms

Complementary

Electrical durability	100000 cycles
Minimum switching current	5 mA for 24 V DC
Maximum switching current	2 A at 250 V AC on inductive load, $\cos \phi = 0.4$ and $L/R = 5$ ms 2 A at 30 V DC on inductive load, $\cos \phi = 0.4$ and $L/R = 5$ ms 5 A at 250 V AC on resistive load, $\cos \phi = 1$ and $L/R = 5$ ms 5 A at 30 V DC on resistive load, $\cos \phi = 1$ and $L/R = 5$ ms
Electrical connection	Screw terminal block, 1.5 mm ² / AWG 16, 0.5 N.m
Product weight	0.4 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.