

**Modlink MSDD set contains: Frame 4000-68522-0000003**

Insert 4000-68000-0150000 + 4000-68000-0940000

## Link to Product

### Illustration



Product may differ from Image

### Frame

suitable for mounting with wall thickness	1...5 mm
Protection	IP65
Temperature range	-30...+70 °C (storage temperature -30...+80 °C)
Housing	Frame: plastic PA black, cap: plastic PC transparent

### RJ45

Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

### USB

Operating current	1.5 A
-------------------	-------

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

Specification	USB: 3.0 (max. 5 Gbit/s)
Locking of ports	Snap In
Operating voltage	48 V AC/DC
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC

**France (UTE-NF)**

Connection	Spring clamp terminals: max. 2× 2.5 mm <sup>2</sup> (AWG 14)
Operating current	10...16 A
No. of poles	2 + PE
Operating voltage	250 V AC

**Shielding plate**

Tightening torque	0.9 Nm ±0.1
Connection	Threaded hole M4

**Commercial data**

country of origin	DE
customs tariff number	85366990
EAN	4048879841368
Packaging unit	1.000