

Modlink MSDD-set: Frame 4000-68113-0000000,

insert 4000-68000-0960000

[Link to Product](#)**Illustration**

Product may differ from Image

Frame

suitable for mounting with wall thickness	1...5 mm
Protection	IP65
Temperature range	-10...+60 °C (storage temperature -25...+60 °C)
Housing	Zinc die-casting, with surface finishing

RJ45

Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

USB

Operating current	max. 500 mA
-------------------	-------------

Specification	USB: 2.0 (max. 480 Mbit/s)
---------------	----------------------------

Locking of ports	Snap In
------------------	---------

Operating voltage	48 V AC/DC
-------------------	------------

Operating voltage (UL Rating)	42.4 V DC
-------------------------------	-----------

Shielding plate

Tightening torque	0.9 Nm \pm 0.1
-------------------	------------------

Connection	Threaded hole M4
------------	------------------

Commercial data

country of origin	DE
-------------------	----

customs tariff number	85366990
-----------------------	----------

EAN	4048879432375
-----	---------------

eClass	27189217
--------	----------

Packaging unit	1.000
----------------	-------