

## MODLINK MSDD DATA INSERT

1×SUB-D25 fem./sold. + 1×RJ45 + 1×USB-A fem./fem.

USB (form A); SUB-D25; RJ45

1× USB 2.0 (female/female) form A

1× SUB-D25 (female/solder connection)

1× RJ45, 8-pole metal, CAT5e (female/female)

### Link to Product

#### Illustration



Product may differ from Image

#### General data

Dimensions H×W×D 88×51×45 mm

#### RJ45

Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

#### USB

Operating current	max. 500 mA
Specification	USB: 2.0 (max. 480 Mbit/s)
Locking of ports	Snap In
Operating voltage	48 V AC/DC
Operating voltage (UL Rating)	42.4 V DC

#### Shielding plate

Tightening torque	0.9 Nm ±0.1
Connection	Threaded hole M4

#### SUB-D25

Locking of ports	UNC 4...40 bolt
Operating current	3 A
Connection rear side	SUB-D (solder connection)
Connection front side	SUB-D (female)
Operating voltage	48 V AC/DC
Operating current (UL Rating)	max. 175 mA
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

No. of poles 25-pole

**Commercial data**

country of origin	DE
customs tariff number	85366990
EAN	4048879037501
eClass	27189217
Packaging unit	1.000