

**Emparro 20-3x360-500/24 S**

Screw mounting

INPUT: 3× 324...572 V AC / 450...745 V DC

OUTPUT: 24...28 V DC

Current: 20 A

[Link to Product](#)**Illustration**

Product may differ from Image

**General data**

Standards	IEC 61010-2-201, EN 61204-3, EN 55011 B, EN 61000-3-2, SEMI F47
Mounting method	4 hole screw mounting
Temperature range	-40...+70 °C, ...+70 °C derating (storage temperature -40...+85 °C)
Relative humidity	5...95%, no condensation
Protection	IP20
Efficiency	94.8% (3× 400 V AC); 94.5% (3× 480 V AC)
Connection	Push-In spring clamp terminals
Dimensions H×W×D	143×65×167 mm

**Output**

Output voltage	24 V DC (SELV), ±1%; 24...28 V adjustable
Power Boost	I <sub>out</sub> N × 150% (min. 5 s)
LED display	LED (green): OK; LED (red): overload, overheating or short-circuit
Output current	15 A (70 °C); 20 A (60 °C); 24 A (45 °C)
Mains failure bridging time	min. 40 ms (3× 500 V AC)
Ripple	max. 20 mV eff/rms
Spikes	max. 90 mV ss/pp
Unit protection	short-circuit and overload protected, permanently by 20% (to 45 °C)
Parallel usage/serial usage	max. 3 units

**Input**

Input voltage	3× 324...572 V AC/450...745 V DC
Input current	1.3 A (3× 360 V AC); 1.0 A (3× 500 V AC)

Inrush current after 1 ms	max. 13 A (3× 500 V AC)
---------------------------	-------------------------

Power factor	0.65 (3× 500 V AC)
--------------	--------------------

Frequency	50..60 Hz
-----------	-----------

Input fuse (internal)	3× 6.3 A (T)
-----------------------	--------------

**Commercial data**

country of origin	CZ
-------------------	----

customs tariff number	85044090
-----------------------	----------

EAN	4048879669023
-----	---------------

eClass	27049002
--------	----------

Packaging unit	1.000
----------------	-------