

## MODLINK MSDD DATA INSERT

1×SUB-D9 fem./fem. + 1×RJ45 + 1×USB-A fem./fem.

RJ45; USB (A); SUB-D9  
 1× RJ45, 8-pole metal, CAT5e (female/female)  
 1× USB 3.0 (female/female) form A  
 1× SUB-D9 (female/female)

### Link to Product

#### Illustration



Product may differ from Image



#### General data

Dimensions H×W×D 88×51×70.4 mm

#### RJ45

Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

#### SUB-D9

Connection rear side	SUB-D (female)
Operating current (UL Rating)	max. 175 mA
Connection front side	SUB-D (female)
Locking of ports	UNC 4...40 bolt
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current	3 A
No. of poles	9-pole
Operating voltage	48 V AC/DC

#### USB

Operating current	1.5 A
Specification	USB: 3.0 (max. 5 Gbit/s)

Locking of ports	Snap In
Operating voltage	48 V AC/DC
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC

**Shielding plate**

Tightening torque	0.9 Nm $\pm$ 0.1
Connection	Threaded hole M4

**Commercial data**

country of origin	CZ
customs tariff number	85366990
EAN	4048879037532
eClass	27189217
Packaging unit	1.000