



RMME 11/24 AC/DC INPUT RELAIS

IN: 24 VAC/DC - OUT: 125 VAC/DC / 1 A

1 relay; 1 NO contact
 1 A
 24 V AC/DC
 Screw terminals

[Link to Product](#)**Illustration**

Product may differ from Image

General data

Mounting method	DIN-rail mountable TH35 or G32 (EN 60715)
Temperature range	-20...+60 °C
Test isolation voltage	1.5 kV
Mech./ elect. life	100 000 000 switching cycles/load dependent
Dimensions HxWxD	56x12x65 mm

Output

Min. load current	1 mA
Contact material	Pd Ni-Au Rh
Energize/release/contact bounce time	10/10/1 ms
Switching voltage	max. 125 V AC/DC

Switching frequency	max. 15 Hz
Power rating (voltage dependent)	max. 60 VA/30 W
Switching current per output	max. 1 A
Input	
Connection voltage - current	24 V AC/DC (19.2...30 V AC/DC) - 6 mA
LED display	LED (yellow)
Utilization category	
AC-15	1 A (24 V AC); 0.5 A (125 V AC)
DC-13	1 A (24 V DC); 0.5 A (125 V DC)
Commercial data	
country of origin	CZ
customs tariff number	85364900
EAN	4048879027465
eClass	27371001
Packaging unit	1.000