

**Modlink MSDD set contains:Frame 4000-68514-0000001**

Insert 4000-68000-1410000

## Link to Product

### Illustration



Product may differ from Image



### Frame

suitable for mounting with wall thickness	1...5 mm
Protection	IP65
Temperature range	-30...+70 °C (storage temperature -30...+80 °C)
Housing	Frame: plastic PA black, cap: plastic PBT gray

### RJ45

Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45

Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

**SUB-D9**

Connection rear side	SUB-D (female)
Operating current (UL Rating)	max. 175 mA
Connection front side	SUB-D (female)
Locking of ports	UNC 4...40 bolt
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current	3 A
No. of poles	9-pole
Operating voltage	48 V AC/DC

**Shielding plate**

Tightening torque	0.9 Nm $\pm$ 0.1
Connection	Threaded hole M4

**Commercial data**

country of origin	DE
customs tariff number	85366990
EAN	4048879691819
eClass	27189234
Packaging unit	1.000