

MODLINK MSDD DATA INSERT

1xSUB-D9 fem./male + 1xRJ45 + 1xUSB-A fem./male 2m

SUB-D9; RJ45; USB (form A)

1 × SUB-D9 (female/male)

1 × RJ45, 8-pole metal, CAT5e (female/female)

1 × USB 2.0 (female/female/2.0 m cable) form A shielded

Link to Product

Illustration



Product may differ from Image

General data

Dimensions H×W×D 87.5×50.7×60.5 mm

RJ45

Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

SUB-D9

Connection rear side	SUB-D (male)
Operating current (UL Rating)	max. 175 mA
Connection front side	SUB-D (female)
Locking of ports	UNC 4...40 bolt
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current	3 A
No. of poles	9-pole
Operating voltage	48 V AC/DC

USB

Operating current	max. 500 mA
Specification	USB: 2.0 (max. 480 Mbit/s)
Locking of ports	Snap In
Operating voltage	48 V AC/DC
Operating voltage (UL Rating)	42.4 V DC

Shielding plate

Tightening torque	0.9 Nm \pm 0.1
Connection	Threaded hole M4

Commercial data

country of origin	DE
customs tariff number	85366990
EAN	4048879800907
eClass	27189217
Packaging unit	1.000