

Main

Product or component type	Passive filter
Product specific application	Reduction of current harmonics

Complementary

Range compatibility	Altivar 61 Altivar 71
[Us] rated supply voltage	480 V (+/- 10 %)
Power supply frequency	60 Hz (tolerance: +/- 5 %)
Quantity per drive	2 filters per drive for ATV71HC25N4 2 filters per drive for ATV61HC25N4 1 filter per drive for ATV71HC13N4 1 filter per drive for ATV61HC13N4
[In] rated current	217 A
Network number of phases	3 phases
THDI	10 % for ATV71HC25N4 ATV71H motor: 250 kW / 400 hp 10 % for ATV71HC13N4 ATV71H motor: 132 kW / 200 hp 10 % for ATV61HC25N4 ATV61H motor: 250 kW / 400 hp 10 % for ATV61HC13N4 ATV61H motor: 132 kW / 200 hp
Max current	1.5 x nominal current
Efficiency	98 %
Cos phi	0.99 at 100 % of line current 0.85 at 75 % of line current 1 at 150 % of line current
Electrical connection	Bare wires, Ø = 16.5 mm
Electrical insulation class	Class F
Product weight	119 kg

Environment

IP degree of protection	IP20
Relative humidity	5...85 % without condensation
Ambient air temperature for operation	5...40 °C without current derating > 40...55 °C with current derating 3 % per °C
Ambient air temperature for storage	> -25...55 °C
Operating altitude	> 1000...4000 m with current derating 5 % per 1000 m <= 1000 m without current derating

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.