



ACTIVE BRAKE RECTIFIER V 1.3

IN: 24 VDC - OUT: 200 VDC / 0,75 A

24 V DC (ON: > 16 V DC; OFF: < 12 V DC)

OUTPUT: 180, 205, 215 V DC

Spring clamp terminals

[Link to Product](#)**Illustration**

Product may differ from Image

**General data**

Mounting method	DIN-rail mountable (EN 60715)
Temperature range	-25...+55 °C
Protection	IP20
Connection	Spring clamp terminals
Dimensions H×W×D	22.5×75×85 mm

Output

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

Output voltage	205 V DC (230 V AC); 180 V DC (400 V AC); 215 V DC (480 V AC)
Switching frequency	max. 2.5 Hz
Output current	max. 0.75 A

Input

Input voltage	L1-N (230 V AC); L1-L2 (400 V AC); L1-L2 (480 V AC)
Invers-polarity protection	yes
Control voltage	24 V DC (ON: > 16 V DC; OFF: < 12 V DC)
LED display	LED (green)
Input current	max. 0.8 A

Commercial data

country of origin	CZ
customs tariff number	85044082
EAN	4048879404150
eClass	27371604
Packaging unit	1.000