

**MODLINK MSDD SINGLE COMBI INSERT USA NEMA 1-15**

1xSUD-D25 female/male + 1xRJ45 female/female

1 × NEMA 1-15 (plug-solder connection)  
 1 × RJ45, 8-pole metal, CAT5e (female/female)  
 1 × SUB-D25 (female/male)

[Link to Product](#)**Illustration**

Product may differ from Image

**General data**

Dimensions HxWxD	88x51x30 mm
------------------	-------------

**RJ45**

Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

**USA**

Operating current	15 A
Operating voltage	125 V AC
No. of poles	2 + PE
Connection	Plug-solder connection: 4.8x0.5 mm

**SUB-D25**

Locking of ports	UNC 4...40 bolt
Operating current	3 A
Connection rear side	SUB-D (male)
Connection front side	SUB-D (female)
Operating voltage	48 V AC/DC
Operating current (UL Rating)	max. 175 mA
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC

No. of poles 25-pole

**Commercial data**

country of origin	DE
customs tariff number	85366990
EAN	4048879037242
eClass	27189217
Packaging unit	1.000