

MODLINK MSDD SINGLE COMBI INSERT BRAZIL

1x SUB-D9 ST/BU

1x Brazil
1x SUB-D9 (male/female)
1x SUB-D9 cut-out

[Link to Product](#)**Illustration**

Product may differ from Image

General data

| | |
|---------------------------|---------------------------------------|
| Protection | IP20 |
| Dimensions H×W×D | 87.5×50.7×30.7 mm (3.44×1.99×1.21 in) |
| Temperature range | +5...+35 °C |
| Storage temperature range | +5...+35 °C |

SUB-D9

| | |
|-------------------------------|------------------------|
| Operating voltage | 48 V AC/DC |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC |
| Operating current | 3 A |
| Operating current (UL Rating) | max. 175 mA |
| No. of poles | 9-pole |
| Connection front side | SUB-D (male) |
| Connection rear side | SUB-D (female) |
| Locking of ports | UNC 4...40 bolt |

Shielding plate

| | |
|-------------------|------------------|
| Connection | Threaded hole M4 |
| Tightening torque | 0.9 Nm ±0.1 |

Commercial data

| | |
|-----------------------|---------------|
| country of origin | DE |
| customs tariff number | 85366990 |
| EAN | 4048879601160 |
| eClass | 27189217 |
| Packaging unit | 1 |