



MST 1-PHASE CONTROL AND ISOLATION TRANSFORMER

P: 4000VA IN: 208...550VAC OUT: 2x115VAC

Single-phase - Control and Isolation Transformers
 4000 VA
 Isolation class T 40/B
 Other voltages on request.

[Link to Product](#)**Illustration**

Product may differ from Image

**General data**

Standards	EN 61558-1, EN 61558-2-4, EN 62041 category 0
Mounting method	Long-hole mounting
Temperature range	-20...+40 °C (storage temperature -40...+80 °C)
Test isolation voltage	4 kV (prim./sec.)
Drill hole Ø	9×14 mm
Fixing centers a×b×c	200×174×9 mm

The information in this brochure has been compiled with the utmost care.
 Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

Dimensions H×W×D 213×197×250 mm

Output

Output voltage 1× 230, 1× 115, 2× 115 V AC
Output rating 4000 VA

Input

Input voltage 208, 230, 380, 400, 420, 440, 460, 480, 500, 525, 550 V AC
Inrush current 372 A (208 V AC); 141 A (550 V AC)
Short-circuit current 960 A (208 V AC); 367 A (550 V AC)
Input current 20 A (208 V AC); 7.7 A (550 V AC)
Frequency 50...60 Hz

Commercial data

country of origin CZ
customs tariff number 85043200
EAN 4048879375542
eClass 27031302
Packaging unit 1.000