



M16 MALE, 90°

PUR 8x0.25 + 2x0,5 black 2m

Male 90°
M16, 14-pole
partly used
with cable sleeves
Further cable lengths on request.

[Link to Product](#)**Illustration**

P	white
J	green
T	yellow
S	gray
G	pink
R	red
E	black
O	violet
A	brown 0.75 mm ²
M	
L	blue 0.75 mm ²
U	

Male

Product may differ from Image

Form

Form 16851

Technical Data

Operating voltage max. 24 V AC/DC

General data

Temperature range -25...+85 °C, depending on cable quality

CablesNo./diameter of wires 8 x 0.25 + 2 x 0.5 mm²

Wire isolation PVC (wh, gn, ye, gr, grpk, rdbl, whgn, brgn; br, bl)

Outer Ø 8.0 mm ±5%

The information in this brochure has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

Cable number	959
Jacket Color	black
Temperature range (fixed)	-25...+70 °C
Temperature range (mobile)	-5...+70 °C
Bend radius (moving)	15× outer Ø
Material (jacket)	PUR/PVC
Commercial data	
country of origin	DE
customs tariff number	85444290
EAN	4048879196703
eClass	27279218
Packaging unit	1.000