

**M12 female 90° A-cod. with cable LED**

PVC 5x0.34 gy UL/CSA 5m

Female 90°

M12, 5-pole

3x LED (PNP)

Art-No. 7005 - M12 Lite - (plastic hexagonal screw) on request


Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

[Link to Product](#)

**Illustration**




(\* for cable type 126, 732, 219, 619)



Product may differ from Image

**Female**



\* only for products with UL/CSA approved cable

**Form**

Form 12441

**Technical Data**

|  |   |
|--|---|
| Operating voltage                                      | 24 V DC $\pm 25\%$  |
| Operating voltage (only UL listed)                     | max. 30 V DC  |
| Rated surge voltage                                    | 0.8 kV  |
| Operating current per contact                          | max. 4 A  |
| Material group   | IEC 60664-1, category I   |
| Coding   | A-coded   |
| LED display  | LED (green): Power / LED (yellow): (S1) / LED (white): Signal (S2) port 1...4 |
| Locking of ports                                       | Screw thread (M12 $\times$ 1 mm) recommended torque 0.6 Nm, self-securing     |
| Compression gland                                      | M12 (SW13)  |
| Protection   | IP65, IP66K, IP67 inserted and tightened (EN 60529)                           |
| Material   | PUR   |
| Locking material                                       | Zinc die casting, nickel-plated   |
| suitable for corrugated tube (internal $\varnothing$ ) | 10 mm   |

#### General data

|                   |  |
|-------------------|--|
| Standards         | DIN EN 61076-2-101 (M12)                 |
| Pollution Degree  | 3  |
| Temperature range | -25...+85 °C, depending on cable quality |

#### Cables

|                                     |   |
|-------------------------------------|---|
| No./diameter of wires               | 5 $\times$ 0.34 mm <sup>2</sup>                 |
| Wire isolation                      | PVC (br, wh, bl, bk, gnye)                      |
| Outer $\varnothing$                 | 5.2 mm $\pm 5\%$                                |
| Cable identification                | 215   |
| Cable Type                          | 1 (PVC)   |
| Approval (cable)                    | UL (AWM-Style 2464/1731), CSA                   |
| Cable weight [g/m]                  | 48,4 g  |
| Material (wire)                     | Cu wire, bare                                   |
| Resistor (core)                     | max. 60 $\Omega$ /km (20 °C)                    |
| Single wire $\varnothing$ (core)    | 0.15 mm   |
| Construction (core)                 | 19 $\times$ 0.15 mm (multi-strand wire class 5) |
| Diameter (core)                     | 5 $\times$ 0.34 mm <sup>2</sup>                 |
| AWG                                 | similar to AWG 22                               |
| Material (wire isolation)           | PVC   |
| Material property (wire isolation)  | CFC-, cadmium-, silicone- and lead-free         |
| Shore hardness (wire isolation)     | 45 $\pm 5$ D                                    |
| Wire- $\varnothing$ incl. isolation | 1.25 mm $\pm 5\%$                               |
| Color/numbering of wires            | br, bk, bl, wh, gnye longitudinally striped     |
| Stranding combination               | 5 wires twisted around central filler           |
| Shield                              | no  |
| Material (jacket)                   | PVC   |
| Material property (jacket)          | CFC-, cadmium-, silicone- and lead-free         |
| Shore hardness (jacket)             | 85 $\pm 5$ A                                    |
| Outer- $\varnothing$ (jacket)       | 5.2 mm $\pm 5\%$                                |
| Color (jacket)                      | gray  |
| Jacket Color                        | gray  |
| chemical resistance                 | good resistance to oil, gasoline and chemicals  |
| thermal resistance                  | flame retardant UL 1581 VW1 / CSA FT1           |
| Nominal voltage                     | UL 300 V AC                                     |
| Test voltage                        | 2000 V AC                                       |
| Current load capacity               | to DIN VDE 0298-4                               |
| Temperature range (fixed)           | -30...+80 °C                                    |
| Temperature range (fixed)           | -30...+80 °C                                    |
| Temperature range (mobile)          | -5...+80 °C                                     |
| Temperature range (mobile)          | -5...+80 °C                                     |

|                      |              |
|----------------------|--------------|
| Bend radius (fixed)  | 5× outer Ø   |
| Bend radius (moving) | 10× outer Ø  |
| Bend radius (moving) | 10× outer Ø  |
| Material (jacket)    | PVC (UL/CSA) |

**Commercial data**

|                       |               |
|-----------------------|---------------|
| country of origin     | DE            |
| customs tariff number | 85444290      |
| EAN                   | 4048879202299 |
| eClass                | 27279218      |
| Packaging unit        | 1.000         |