

MVP12-P6 DIO8 DIO8 8xM12A IOLB12 B0

IO-Link Class B Hub

IO-Link hub in 50 mm plastic housing

1 × M12 IO-Link Class B


8 × M12 I/O

16 configurable digital inputs/outputs

Galvanically isolated voltage groups

Preconfigured parameter range

Connection cables are in the online shop under "Connection Technology".

Link to Product**Illustration**

Product may differ from Image

Technical Data

Installation height	max. 3000 m above sea level
Operating voltage (UA)	24 V DC (18...30 V DC)
Operating voltage (US)	24 V DC (18...30 V DC)
	max. 4 A
	max. 4 A
	yes
Current consumption	max. 50 mA
LED display	US-IOL: sensor power supply IOL (green: OK)

General data

Mounting method	2-hole screw mounting
Temperature range	-25...+70 °C (storage temperature -40...+85 °C)
Protection	IP68
Dimensions HxWxD	126x50x34.5 mm

Output

Switching current per output	max. 2 A
------------------------------	----------

Input

Type	Type 1 + type 3
Input filter	1 ms
	24 V DC (EN 61131-2), max. 0.5 A, short-circuit and overload-protected

IO-Link

Specification	IO-Link V1.1.2, compatible with: IO-Link V1.1.3
Port Class	B
IO-Link	Device
Operating modes	COM3 (230.4 kBaud)
Cycle time	min. 1 ms
	2 Byte (Inputs), 2 Byte (Outputs)

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

Murrelektronik Ltd. | 5 Albion Street, Pendlebury Industrial Estate, Swinton | Manchester M27 4FG | Fon +44 161 728 3133 | Fax +44 161 728 3130 | shop@murrelektronik.co.uk | shop.murrelektronik.co.uk

Parameterization	
PIN 4	Input/output/DIO (port X0...X7)
PIN 2	Input/output/DIO (port X0...X7)
Connections	
IO-Link	M12, 5-pole, A-coded
I/O ports	M12, 5-pole, A-coded
Diagnostic	
Communication status	via LED
Diagnostic via LED	per module and channel
Actuator warning	yes
Monitoring - under voltage	yes
Monitoring - no voltage	yes
Short-circuit and overload	yes
Commercial data	
country of origin	DE
customs tariff number	85389099
EAN	4048879865043
eClass	27242604
Packaging unit	1.000