



Main

Range of product	Lexium 32
Product or component type	Encoder interface module
Accessory / separate part type	Card with digital output
Accessory / separate part category	Connection accessory
Accessory / separate part destination	Machine encoder
Encoder type	A/B/I BISS EnDat 2.2 SSI

Complementary

Product compatibility	Lexium 32M
[Us] rated supply voltage	12 V for SSI encoder 5 V for A/B/I encoder 5 V for BISS encoder 5 V for EnDat 2.2 encoder
Electrical connection	1 female connector high definition SUB-D, 15 pin(s)

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Available Download End Of Life Manual

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.