

Modlink MSDD-set: Frame 4000-68522-0000001,

insert 4000-68000-4310003

[Link to Product](#)**Illustration**

Product may differ from Image

Frame

suitable for mounting with wall thickness	1...5 mm
Protection	IP65
Temperature range	-30...+70 °C (storage temperature -30...+80 °C)
Housing	Frame: plastic PA black, cap: plastic PC transparent

RJ45

Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

USB

Operating current	1.5 A
-------------------	-------

Specification	USB: 3.0 (max. 5 Gbit/s)
Locking of ports	Snap In
Operating voltage	48 V AC/DC
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC

France (UTE-NF)

Connection	Screw terminals: max. 2× 4 mm ² (AWG 12)
Operating current	16 A
No. of poles	2 + PE
Operating voltage	250 V AC

Shielding plate

Tightening torque	0.9 Nm ±0.1
Connection	Threaded hole M4

Commercial data

country of origin	DE
customs tariff number	85366990
EAN	4048879445900
eClass	27189217
Packaging unit	1.000