



Main

Range compatibility	PacDrive 3
Product or component type	Servo motor
Device short name	SH3.....P

Complementary

Maximum mechanical speed	3800 rpm
[Us] rated supply voltage	115...480 V
Network number of phases	Three phase
Continuous stall current	33.2 A
Continuous stall torque	94.4 N.m at 115...480 V three phase
Peak stall torque	330 N.m at 115...480 V three phase
Nominal output power	10100 W at 480 V three phase 10620 W at 400 V three phase 7790 W at 230 V three phase 4450 W at 115 V three phase
Nominal torque	40.2 N.m at 480 V three phase 50.7 N.m at 400 V three phase 74.4 N.m at 230 V three phase 84.9 N.m at 115 V three phase
Nominal speed	2400 rpm at 480 V three phase 2000 rpm at 400 V three phase 1000 rpm at 230 V three phase 500 rpm at 115 V three phase
Maximum current Irms	136.1 A
Shaft end	Smooth shaft
Shaft diameter	38 mm
Shaft length	80 mm
Key width	10 mm
IP degree of protection	IP67 (housing) conforming to EN/IEC 60034-5 IP65 (shaft bushing) conforming to EN/IEC 60034-5 IP65 (motor) conforming to EN/IEC 60034-5
Encoder type	Absolute multiturn SinCos Hiperface
Speed feedback resolution	128 periods
Holding brake	With
Holding torque	80 N.m
Mounting support	International standard flange
Motor flange size	205 mm
Electrical connection	Rotatable right angled connector
Torque constant	2.76 N.m/A at -20...40 °C
Back emf constant	172 V/krpm at 20 °C

Number of motor poles	5
Rotor inertia	206 kg.cm ²
Stator resistance	0.2 Ohm at -20...40 °C
Stator inductance	6.3 mH at -20...40 °C
Maximum radial force Fr	3120 N at 3000 rpm 3570 N at 2000 rpm 4500 N at 1000 rpm
Maximum axial force Fa	740 N
Type of cooling	Natural convection
Length	538.5 mm
Centring collar diameter	180 mm
Centring collar depth	4 mm
Number of mounting holes	4
Mounting holes diameter	14 mm
Circle diameter of the mounting holes	215 mm
Product weight	70.6 kg

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1036 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Need no specific recycling operations