



Main

Range of product	PacDrive 3
Product or component type	Double drive
Component name	LXM62

Complementary

Product compatibility	Servo motor MH3 100 mm 1 optimized in terms of torque and speed Servo motor MH3 70 mm 3 optimized in terms of torque and speed Servo motor MH3 70 mm 2 optimized in terms of torque and speed Servo motor SH3 140 mm 1 optimized in terms of high torque Servo motor SH3 100 mm 3 optimized in terms of high torque Servo motor SH3 100 mm 2 optimized in terms of high torque Servo motor SH3 100 mm 2 optimized in terms of torque and speed Servo motor SH3 100 mm 1 optimized in terms of torque and speed Servo motor SH3 70 mm 3 optimized in terms of torque and speed Servo motor SH3 70 mm 2 optimized in terms of torque and speed Servo motor SHS
[Us] rated supply voltage	24 V DC
Continuous output current	5 A 4 kHz
Output current 3s peak	15 A 4 kHz
Continuous power	2.4 kW
Overvoltage category	III
Electrical connection	Terminal 0.2...6 mm ² AWG 24...AWG 10 CN7 Terminal 0.75...16 mm ² AWG 18...AWG 6 CN6 Terminal 0.5...16 mm ² AWG 20...AWG 6 CN5 Terminal 0.2...15 mm ² AWG 24...AWG 16 CN4
Tightening torque	2.5 N.m CN1
Number of inputs	2 touch probe 2 digital
Discrete input voltage	24 V DC
Number of outputs	2 digital
Discrete output voltage	24 V DC
Safety function	STO (safe torque off)
Physical interface	SERCOS III
Product weight	3 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	EN 61800-3 EN 61800-5-1 EN 61800-5-2 EN/ISO 13849-1 IEC 61508 EN 62061 UL 508C IEC 62061 CSA C22.2 No 14 EN/ISO 13849-2
Product certifications	CE CSA TÜV UL EAC
IP degree of protection	IP20 EN/IEC 60529
Vibration resistance	10 m/s ² EN/IEC 60721-3-3
Shock resistance	100 m/s ² EN/IEC 60721-3-3
Pollution degree	2 EN/IEC 61800-5-2
Environmental characteristic	3K3 IEC 60721-3-3
Relative humidity	5...85 %
Ambient air temperature for operation	5...55 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1136 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Available