

Modlink MSDD-set: Frame 4000-68524-0000001,

insert 4000-68000-4300003

Link to Product

Illustration



Product may differ from Image

Frame

suitable for mounting with wall thickness	1...5 mm
Protection	IP65
Temperature range	-30...+70 °C (storage temperature -30...+80 °C)
Housing	Frame: plastic PA black, cap: plastic PBT gray

General data

Dimensions HxWxD	88x116x72 mm
------------------	--------------

RJ45

Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC

Specification CAT5e, Class D, 100 MHz, (EN 50173-1)

USB

Operating current	1.5 A
Specification	USB: 3.0 (max. 5 Gbit/s)
Locking of ports	Snap In
Operating voltage	48 V AC/DC
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC

Germany (VDE)

Connection	Spring clamp terminals: max. 2x 2.5 mm ² (AWG 14)
Operating voltage	250 V AC
No. of poles	2 + PE
Operating current	16 A

Commercial data

country of origin	DE
customs tariff number	85366990
EAN	4048879460903
eClass	27144001
Packaging unit	1.000