

Industrial Ethernet Switch - FL SWITCH 4012T-2GT-2FX - 2891063

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Managed Ethernet switch with 12 RJ45 ports at 10/100 Mbps, two RJ45 ports at 10/100/1000 Mbps and two SC-D fiber optic ports at 100 Mbps. Wide operating temperature of -40°C ... +75°C.

Product Description


FL SWITCH 4000 managed industrial Ethernet switches combine Gigabit interfaces with extensive network performance for the most demanding applications. Security features with complete IEEE redundancy (STP/RSTP/MST) and 15 ms recovery time extended ring redundancy optimize network uptime. Unique web customization provides a simplified user interface for today's applications and scalable functionality for future needs. A comprehensive mix of 10/100 Mbps and Gigabit fiber optic connections combine performance with installed cost savings.

Your advantages

- ✓ Twelve 10/100 Mbps ports for device connections, two Gigabit RJ45 ports for network trunk lines, and two 100 Mbps multi-mode fiber optic SC interfaces for remote connections
- ✓ -40 °C to 75 °C ambient temperature
- ✓ Extensive web diagnostics with configurable LED and remote alarm contacts
- ✓ Secure web-based and SNMP-based management
- ✓ Unique cleanup function hides unused configuration pages, reducing complexity, maintenance and startup times



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 764315
GTIN	4046356764315
Weight per Piece (excluding packing)	1,750.000 g
Custom tariff number	85176200
Country of origin	Taiwan