

## D-SUB bus connector - SUBCON-PLUS-CAN/PG - 2708119

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



D-SUB connector, 9-pos. socket, 35° cable entry, bus system: CAN, CANopen<sup>®</sup>, SafetyBUS p up to 1 Mbps, with PG D-SUB socket for connecting a programming device, termination resistor can be switched on via slide switch, pin assignment: 2, 3, 7, 9; screw terminal blocks

#### **Product Description**

The SUBCON-PLUS-CAN/... D-SUB series is specifically designed for use in CAN systems. Under field conditions, it enables the quick and easy connection of the incoming and outgoing bus line.

The terminating resistor is already integrated in all versions. It can be connected externally by means of a slide switch. At the same time, the outgoing bus segment is switched off. This makes it easy to start up segment by segment while incorrect terminations are avoided.

A special feature of the 35° angled connector is that the internal connection unit can be turned round. Whether the cable is to be inserted from the right or left can thus be decided on-site.

#### Your advantages

- Assembly under field conditions
- Flexibility in terms of cable entry selection
- High transmission speed
- ☑ Suitable for bus cables according to CiA Draft Recommendation 303-1 with an outside diameter of 8 mm
- Change to the D-SUB orientation through a reversible connection block



### Key Commercial Data

Packing unit	1 pc
GTIN	4 046356 041331
GTIN	4046356041331
Weight per Piece (excluding packing)	41.700 g
Custom tariff number	85366990



# D-SUB bus connector - SUBCON-PLUS-CAN/PG - 2708119

Country of origin	Germany
-------------------	---------

Phoenix Contact 2022 © - all rights reserved http://www.phoenixcontact.com