

FO converters - PSI-MOS-RS422/FO 660 T - 2708384

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




FO converter with integrated optical diagnostics, alarm contact, for RS-422/RS-485 4-wire/INTERBUS up to 2 Mbps, T-coupler with two FO interfaces (FSMA), 660 nm, for polymer/PCF fiber cable

Your advantages

- ✓ Supply voltage routed through via DIN rail connectors
- ✓ Connections can be plugged in via a COMBICON screw terminal block
- ✓ Redundant power supply possible by means of optional system power supply unit
- ✓ High-quality electrical isolation between all interfaces (INTERBUS // FO ports // supply // DIN rail connector)
- ✓ Approved for use in zone 2
- ✓ Floating switch contact for advance warning of critical FO paths
- ✓ Integrated optical diagnostics for continuous monitoring of FO paths
- ✓ Intrinsically safe fiber optic interface (Ex op is) for direct connection to devices in zone 1
- ✓ Automatic data rate detection for all data rates up to 2 Mbps



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 974084
GTIN	4017918974084
Weight per Piece (excluding packing)	236.900 g
Custom tariff number	85176200
Country of origin	Germany