

Timer module - PLC-OSC-LPE-24DC/48DC/100 - 2903171

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



1-channel pulse expansion module, input: 24 V DC, output: 3 - 48 V DC/100 mA, supply: 24 V DC, screw connection

Product Description

DIP switch settings:

Function

- DIP A low - no restart when triggered again (default)
- DIP A high - restart when triggered again
- DIP B low - input pulse time > 2 ms (default)
- DIP B high - input pulse time > 100 μ s

Pulse expansion times

- DIP 1 - 10 ms
- DIP 2 - 20 ms
- DIP 3 - 40 ms
- DIP 4 - 80 ms
- DIP 5 - 160 ms
- DIP 6 - 320 ms
- DIP 7 - 640 ms
- DIP 8 - 1280 ms

No DIP switch set: no switching function for the output

If the input signal is longer than the selected time, the output is switched off after removal of the input signal.

The settings are applied after a voltage reset of the rated control supply voltage.



Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4046356727853
Weight per Piece (excluding packing)	60.000 g
Custom tariff number	85371098

Timer module - PLC-OSC-LPE-24DC/48DC/100 - 2903171

Country of origin	Germany
-------------------	---------

Phoenix Contact 2022 © - all rights reserved
<http://www.phoenixcontact.com>