



Main

| | |
|------------------------------|---|
| Range | TeSys |
| Device short name | LA1SK |
| Product or component type | Auxiliary contact block |
| Product compatibility | LC1SK |
| Auxiliary contacts operation | Instantaneous |
| Pole contact composition | 2 NO |
| Connections - terminals | Screw clamp terminals 2 cable 0.35...1.5 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 0.35...6 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0.35...2.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.5...6 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 1.5...4 mm ² - cable stiffness: solid Screw clamp terminals 1 cable 1.5...6 mm ² - cable stiffness: solid |

Complementary

| | |
|---|---|
| Mounting location | Front side |
| [Ui] rated insulation voltage | 690 V - conforming to CSA C22.2 No 14 690 V - conforming to VDE 0110 group C 690 V - conforming to BS 5424 690 V - conforming to IEC 60947 |
| [Ue] rated operational voltage | 690 V AC <= 400 Hz |
| [Ith] conventional free air thermal current | 10 A at <= 55 °C |
| Associated fuse rating | VDE 0660 IEC 60947 |
| Tightening torque | 0.8 N.m - on screw clamp terminals |
| Width | 27 mm |
| Product weight | 0.022 kg |

Environment

| | |
|---------------------------------------|---|
| Standards | BS 5424 IEC 60947 NF C 63-110 VDE 0660 |
| Product certifications | CSA UL |
| IP degree of protection | IP2x |
| Protective treatment | TC conforming to IEC 60068 |
| Ambient air temperature for operation | -20...50 °C |
| Ambient air temperature for storage | -50...70 °C |
| Operating altitude | 2000 m without derating in temperature |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS | Compliant - since 0718 - Schneider Electric declaration of conformity |