

## Inline terminal - IB IL 24/230 DOR1/W-PC-PAC - 2862178

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline, Relay terminal, Relay output: 1 (floating contacts), 24 V DC, 230 V AC, for switching inductive and capacitive loads, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connector and labeling field

### Product Description

The terminal is designed for use within an Inline station.

It has one floating SPDT relay contact.

The terminal is suitable for switching inductive and capacitive loads.

The terminal can be used in the PELV area and in the AC area.


For switching voltages below 12 V or currents below 100 mA, please use the IB IL 24/230 DOR 1/W-PAC: terminal.

### Your advantages

- Safe isolation in acc. with EN 50178
- Floating connection for one actuator
- Nominal current at the output: 2.2 A
- Total current of the terminal: 2.6 A



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 894665
GTIN	4017918894665
Weight per Piece (excluding packing)	79.700 g
Custom tariff number	85389099
Country of origin	Germany