

Cube67 Valve-Interface, I/O Extension Module

DO16, Open-End, 1,5m

Expansion module

DO16 - Valve (E) 0.5 m


Open cable (0.5 m) 50 mA

Connection cables are in the online shop under "Connection Technology".

Housing fully potted.

Link to Product

Illustration



Product may differ from Image



General data

Mounting method	2-hole screw mounting
Temperature range	0...+55 °C (storage temperature -20...+75 °C)
Protection	IP67
Dimensions HxWxD	150x30x34.5 mm

Output

Actuator supply UA	24 V DC (EN 61131-2), via system connection (max. 4 A)
--------------------	--

Cables

No./diameter of wires	18x 0.25 mm ²
Material (jacket)	PVC

Internal communication

LED display	US: sensor supply and internal supply voltage (green: OK); UA: actuator supply (green: OK)
Current consumption	max. 50 mA

Connections

Fieldbus	via internal system connection
Sensor-system/actuator supply	via internal system connection (max. 2x 4 A)
I/O ports	Open cable (0.5 m) 50 mA

Diagnostic

Communication status	via LED
Diagnostic via LED	per module
Diagnostic via BUS	per module and channel
Actuator warning	per channel via BUS
Monitoring - under voltage	yes
Monitoring - no voltage	yes

Short-circuit and overload yes

Commercial data

country of origin	DE
customs tariff number	85444290
EAN	4048879045230
eClass	27242604
Packaging unit	1.000