

Modlink MSDD-set: Frame 4000-68123-0000000,
insert 4000-68000-0160000 + 4000-68000-1210000

[Link to Product](#)

Illustration



Product may differ from Image

The information in this brochure has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

| Frame | |
|---|--|
| suitable for mounting with wall thickness | 1...5 mm |
| Protection | IP65 |
| Temperature range | -10...+60 °C (storage temperature -25...+60 °C) |
| Housing | Zinc die-casting, with surface finishing |
| RJ45 | |
| Operating current (UL Rating) | max. 175 mA |
| Locking of ports | Snap In |
| Connection front side | RJ45 |
| Connection rear side | RJ45 |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC |
| Specification | CAT5e, Class D, 100 MHz, (EN 50173-1) |
| Germany (VDE) | |
| Connection | Spring clamp terminals: max. 2× 2.5 mm ² (AWG 14) |
| Operating voltage | 230 V AC |
| No. of poles | 2 + PE |
| Operating current | 16 A |
| Commercial data | |
| country of origin | DE |
| customs tariff number | 85366990 |
| EAN | 4048879034524 |
| eClass | 27189217 |
| Packaging unit | 1.000 |