

BRH1103P22A2A

AC servo motors BRH - 12 N.m - 4500 rpm -
untapped shaft - without brake - IP56

Main

Product or component type	Motion servo motors
Component name	BRH
Continuous stall torque	12 N.m
Peak stall torque	18.9 N.m for LXM05AD34N4 18.9 N.m for LXM05BD34N4 18.9 N.m for LXM05CD34N4 21 N.m for LXM05AD28M2 21 N.m for LXM05BD28M2 21 N.m for LXM05CD28M2 30.3 N.m for LXM05AD42M3X 30.3 N.m for LXM05AD57N4 30.3 N.m for LXM05BD42M3X 30.3 N.m for LXM05BD57N4 30.3 N.m for LXM05CD42M3X 30.3 N.m for LXM05CD57N4
Nominal output power	1550 W for LXM05BD42M3X 1550 W for LXM05CD28M2 1550 W for LXM05CD42M3X 1550 W for LXM05AD28M2 1550 W for LXM05AD42M3X 1550 W for LXM05BD28M2 2360 W for LXM05BD57N4 2360 W for LXM05CD34N4 2360 W for LXM05CD57N4 2360 W for LXM05AD34N4 2360 W for LXM05AD57N4 2360 W for LXM05BD34N4
Nominal speed	1500 rpm for LXM05AD28M2 1500 rpm for LXM05AD42M3X 1500 rpm for LXM05BD28M2 1500 rpm for LXM05BD42M3X 1500 rpm for LXM05CD28M2 1500 rpm for LXM05CD42M3X 3000 rpm for LXM05AD34N4 3000 rpm for LXM05AD57N4 3000 rpm for LXM05BD34N4 3000 rpm for LXM05BD57N4 3000 rpm for LXM05CD34N4 3000 rpm for LXM05CD57N4
Maximum mechanical speed	4500 rpm
Product compatibility	LXM05AD28M2 at 230 V single phase LXM05AD34N4 at 400/480 V 3 phases LXM05AD42M3X at 230 V 3 phases LXM05AD57N4 at 400/480 V 3 phases LXM05BD28M2 at 230 V single phase LXM05BD34N4 at 400/480 V 3 phases LXM05BD42M3X at 230 V 3 phases LXM05BD57N4 at 400/480 V 3 phases LXM05CD28M2 at 230 V single phase LXM05CD34N4 at 400/480 V 3 phases LXM05CD42M3X at 230 V 3 phases LXM05CD57N4 at 400/480 V 3 phases
Shaft end	Untapped
IP degree of protection	IP56
Encoder type	Multiturn SinCos Hiperface
Encoder feedback resolution	131072 points/turn x 4096 turns
Holding brake	Without
Mounting support	International standard flange

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Electrical connection	Rotatable right-angled connectors
Number of poles	10

Complementary

Range compatibility	Lexium 05
Switching frequency	8 kHz
Nominal torque	7.5 N.m for LXM05AD34N4 7.5 N.m for LXM05AD57N4 7.5 N.m for LXM05BD34N4 7.5 N.m for LXM05BD57N4 7.5 N.m for LXM05CD34N4 7.5 N.m for LXM05CD57N4 10 N.m for LXM05AD28M2 10 N.m for LXM05AD42M3X 10 N.m for LXM05BD28M2 10 N.m for LXM05BD42M3X 10 N.m for LXM05CD28M2 10 N.m for LXM05CD42M3X
Maximum current I _{rms}	18 A for LXM05AD34N4 18 A for LXM05BD34N4 18 A for LXM05CD34N4 20 A for LXM05AD28M2 20 A for LXM05BD28M2 20 A for LXM05CD28M2 30 A for LXM05AD42M3X 30 A for LXM05AD57N4 30 A for LXM05BD42M3X 30 A for LXM05BD57N4 30 A for LXM05CD42M3X 30 A for LXM05CD57N4
Torque constant	1.06 N.m/A rms at 120 °C
Back emf constant	68.5 V rms/krpm at 120 °C
Rotor inertia	13.1 kg.cm ² without brake 14.4 kg.cm ² with brake
Stator resistance	0.5 Ohm
Stator inductance	3.9 mH
Stator electrical time constant	7.2 ms
Maximum radial force Fr	857 N at 4000 rpm 869 N at 3000 rpm 883 N at 2000 rpm 908 N at 1000 rpm
Maximum axial force Fa	0.2 x Fr
Product weight	10.5 kg

Environment

RoHS EUR conformity date	4Q2009
RoHS EUR status	Will be compliant