

## MST SINGLE-PHASE CONTROL AND ISOLATION TRANSFORMER

P:630VA IN:400VAC±5% OUT:230VAC

Single-phase - Control and Isolation Transformers  
630 VA  
Isolation class T 40/B

### [Link to Product](#)

#### Illustration



Product may differ from Image



#### General data

Standards	EN 61558-1, EN 61558-2-4, EN 62041 category 0
Mounting method	Key-hole mounting
Temperature range	-20...+40 °C (storage temperature -40...+80 °C)
Test isolation voltage	4.7 kV
Fixing centers a×b×c	90.6×122×7 mm
Dimensions H×W×D	115×150×143 mm

#### Output

The information in this brochure has been compiled with the utmost care.  
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

Output voltage	230 V AC
Output rating	630 VA
<b>Input</b>	
Input voltage	400 V AC $\pm$ 5%
Inrush current	25 A (400 V AC)
Short-circuit current	44 A (400 V AC)
Input current	1.77 A (400 V AC)
Frequency	50...60 Hz
<b>Commercial data</b>	
country of origin	CZ
customs tariff number	85043180
EAN	4048879073769
eClass	27031202
Packaging unit	1.000