

**M12 female 0° A-cod.with cable 3LED**

PUR 5x0.34 gy UL/CSA 20m

Female straight

M12, 5-pole

3× LED (PNP)

Art-No. 7005 - M12 Lite - (plastic hexagonal screw) on request

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

[Link to Product](#)

**Illustration**




(\* for cable type 126, 732, 219, 619)



**Female**



Product may differ from Image



\* only for products with UL/CSA approved cable

**Form**

Form 12251

**Technical Data**

|                               |   |
|-------------------------------|---|
| Operating voltage             | 24 V DC $\pm 25\%$  |
| Rated surge voltage           | 0.8 kV  |
| Operating current per contact | max. 4 A  |
| Material group                | IEC 60664-1, category I   |
| Coding                        | A-coded   |
| LED display                   | green, yellow, white  |
| Locking of ports              | Screw thread (M12 $\times$ 1 mm) recommended torque 0.6 Nm, self-securing |
| Compression gland             | M12 (SW13)  |
| Protection                    | IP65, IP66K, IP67 inserted and tightened (EN 60529)                       |
| Material                      | PUR   |
| Locking material              | Zinc die casting, matte nickel plated                                     |

#### General data

|                   |  |
|-------------------|--|
| Standards         | DIN EN 61076-2-101 (M12)                 |
| Pollution Degree  | 3  |
| Temperature range | -25...+85 °C, depending on cable quality |

#### Cables

|                                     |  |
|-------------------------------------|--|
| Cable identification                | 225  |
| Cable Type                          | 2 (PUR/PVC)  |
| Approval (cable)                    | UL (AWM-Style 20549/1731), CSA; CE conform   |
| Cable weight [g/m]                  | 54,78 g  |
| Material (wire)                     | Cu wire, bare  |
| Resistor (core)                     | max. 57 $\Omega$ /km (20 °C)   |
| Single wire $\varnothing$ (core)    | 0.1 mm   |
| Construction (core)                 | 42 $\times$ 0.1 mm (multi-strand wire class 6)   |
| Diameter (core)                     | 5 $\times$ 0.34 mm <sup>2</sup>  |
| AWG                                 | similar to AWG 22  |
| Material (wire isolation)           | PVC  |
| Material property (wire isolation)  | CFC-, cadmium-, silicone- and lead-free  |
| Shore hardness (wire isolation)     | 43 $\pm$ 5 D   |
| Wire- $\varnothing$ incl. isolation | 1.25 mm $\pm 5\%$  |
| Color/numbering of wires            | br, bk, bl, wh, gnye longitudinally striped  |
| Stranding combination               | 5 wires twisted around central filler  |
| Shield                              | no   |
| Material (jacket)                   | PUR/PVC  |
| Material property (jacket)          | CFC-, halogen-, cadmium-, silicone- and lead-free, matt, low-adhesion, machine easy to process, abrasion-resistant, hydrolysis and microbial resistant |
| Shore hardness (jacket)             | 80 $\pm$ 5 A (PVC-under jacket); 85 $\pm$ 5 A (PUR-jacket)   |
| Outer- $\varnothing$ (jacket)       | 5.0 mm $\pm 5\%$   |
| Color (jacket)                      | gray   |
| chemical resistance                 | good resistance to oil, gasoline and chemicals   |
| Nominal voltage                     | UL 300 V AC  |
| Test voltage                        | 2000 V AC  |
| Current load capacity               | to DIN VDE 0298-4  |
| Temperature range (fixed)           | -30...+80 °C   |
| Temperature range (mobile)          | -5...+80 °C  |
| Bend radius (fixed)                 | 10 $\times$ outer $\varnothing$  |
| Bend radius (moving)                | 15 $\times$ outer $\varnothing$  |
| No. of bending cycles (C-track)     | max. 2 Mio. (25 °C)  |
| Travel speed (C-track)              | max. 3.3 m/s   |
| Acceleration (C-track)              | max. 5 m/s <sup>2</sup>  |

#### Commercial data

|                       |          |
|-----------------------|----------|
| country of origin     | CZ       |
| customs tariff number | 85444290 |

|                |               |
|----------------|---------------|
| EAN            | 4048879817271 |
| eClass         | 27279218      |
| Packaging unit | 1.000         |