

**Modlink MSDD-set: Frame 4000-68523-0000001,**

insert 4000-68000-4120000


with touch protection

[Link to Product](#)

#### Illustration



Product may differ from Image



#### Frame

suitable for mounting with wall thickness	1...5 mm
Protection	IP65
Temperature range	-30...+70 °C (storage temperature -30...+80 °C)
Housing	Frame: plastic PA black, cap: plastic ABS metallic

#### General data

Dimensions H×W×D	88×116×72 mm
------------------	--------------

#### RJ45

Operating current (UL Rating)	max. 175 mA
-------------------------------	-------------

The information in this brochure has been compiled with the utmost care.  
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

**Fuse**

Operating voltage	250 V AC/32 V DC
Continuous load	3 A

**USA**

Operating current	15 A
Operating voltage	125 V AC
No. of poles	2 + PE
Connection	Screw terminals: max. 2× 6 mm <sup>2</sup> (AWG 10)

**Commercial data**

country of origin	DE
customs tariff number	85366990
EAN	4048879477970
eClass	27144001
Packaging unit	1.000